



Fire prevention systems



ART.NO.VSN4-LT-IT
4 ZONES CONVENTIONAL FIRE DETECTION PANEL



NOTIFIER
by Honeywell

Conventional 4-Zone Control Unit designed for the installation of small and medium-sized fire detection systems. Material: Painted steel container, Dimensions (mm): 315mm (A) x 380mm (L) x 100mm (P), Weight: about 3Kg (without batteries), Operating temperature -5 to 45 ° C (recommended +5 to 35 ° C), Humidity: 5 to 95% (without condensation), Degree of protection: IP 30, Voltage: 27Vcc ± 7%.

ART.NO.SD-851EA
OPTICAL DETECTOR



NOTIFIER
by Honeywell

Optical smoke detector consisting of an optical chamber sensitive to light diffusion. Programmable sensitivity with external equipment. Prepared for testing by laser remote control. Alarm display LED. Output for alarm repetition. Possibility of addressing via additional module. CPR certificate according to EN54 regulation part 7. Power supply 8-30Vcc. Operating temperature from - 20 to + 60 ° C. Relative humidity up to 95% without condensation.

ART.NO.FD-851RE
RATE - OFF - RISE
THERMAL DETECTOR



NOTIFIER
by Honeywell

Thermovelocimetric detector consisting of a double thermistor. Intervention at 58 ° C. Prepared for testing by laser remote control. Alarm display LED. Output for alarm repetition. Possibility of addressing via additional module. CPR certificate according to EN54 regulation part 5. Power supply 8-30Vcc. Operating temperature from - 20 to + 60 ° C. Relative humidity up to 95% without condensation.

ART.NO.RT-XMST26SCM
SPECIAL THERMAL
DETECTOR
ATEX CERTIFICATE



NOTIFIER
by Honeywell

Thermal detector of the mechanical type of maximum temperature, suitable for industrial applications where it is necessary to use equipment with a high degree of protection, with ADPE container and with regulation of the intervention temperature, programmed at the factory with a range between -20 and + 190 ° C (brass version up to 150 ° C). The programmed intervention temperature must normally be between 10 and 35 ° C above that normally present in the environment. ATEX certificate. Operating voltage up to 48 Vdc. Relative humidity 98% without condensation.

ART.NO.40/40U
FLAME DETECTOR
CERTIFICATE
ATEX E CPR



NOTIFIER
by Honeywell

Optical flame detector sensitive to ultraviolet radiation. Equipped with alarm relay, fault relay and auxiliary relay. 4-20 mA and RS485 output. Alarm signal within 3 seconds with a flame of only 0.1 square meters using ethane. Activation time can be delayed up to 30 seconds. Power supply 18-32 VDC with consumption of 150 mA at rest and 200 mA in alarm. Heated case. ATEX and CPR certificate according to EN 54-10. Operating temperature from -55 ° C to + 75 ° C. ATEX Ex II 2GD case. IP67 protection rating.

Packing: 1/1.

ART.NO.CWSS-RR-S5
OPTICAL / ACOUSTIC
SIGNAL WITH RED LED
EN54-3 / 23



NOTIFIER
by Honeywell

Red siren with red LED flashing light. Complete with standard base. Ideal for applications where a double alarm signal is required. The new sirens have been designed with a new design that includes: a folded trumpet, a high performance LED, an advanced optics and an innovative lens. These features allow the device to have excellent sound quality, an extraordinary omnidirectional light coverage and a very low impact on current consumption, ensuring quality reliability and long life. CPR certified according to EN 54-3 / 23. Operating voltage: 12 to 29Vcc. Average absorption: 49mA @ 29Vdc Class W tone 7. Sound output power: max. 107dB (A) @ 1m (tone 23). Number of tones: 32. Volume setting: medium or high. Cable termination: 0.5-2.5mm². Body material: ABS. Lens Material: PC.

NEW



ART.BA.FLUKE
FLUKE 568 EX
TEMPERATURE
DETECTOR FOR ATEX
ZONES 1/0

Laser Pointer 1-beam, saves up to 99 measurements, including time and date. 4 hours of continuous operation. Infrared temperature range -40 °C to +800 °C (-104 °F to +1.472 °F), Display 0.1 °C / 0.1 °F. Response time for infrared <500 ms
 Distance from the measured point dimension (D: S) 50: 1. Archiving: up to 99 points with time and date. Min / Max / Average / Diff Yes. Digital output adjustment, from 0.1 to 1.00, with 0.01 shots. Accuracy > 0 °C ± 1 °C or 1% always the highest value. Ambient temperature: From ± 0 °C to +50 °C (from +32 °F to +122 °F). 2x AAA power supply, approved type
 Weight: about 365 gr.

Packing: 1

ART.NO.AM1000
CENTRAL ANALOGIC FIRE-FIGHTING 1 LOOP



NOTIFIER
 by Honeywell

Addressed type, each line of the AM1000 control panel allows the connection of 99 detectors and 99 modules, it includes controlled siren output and relay outputs for general alarm and fault. Equipped with a serial output for download / upload programming or for printer, Graphic LCD display with 8 lines of 20 characters each, possibility to program written 16 characters per point and 16 characters per zone, management of 50 zones, 100 groups with logical operators (AND, OR, DEL, etc.). Archive capacity of 500 events. The am1000 fire alarm control panel also allows self-programming of lines with double address recognition and a system to signal maintenance needs for the detectors. CPR certified in accordance with EN-54 parts 2 and 4, Dimensions 366 x 265 x 111, Power supply from 230 Vac mains, Standard power supply 1,8A, Auxiliary current at 24Vcc of 1A, Recharge of two 12Vcc 7 Ah batteries

ART.NO.LCD6000N
DISPLAY LCD REPAV
FOR CENTRALS
AM2000N - AM4000 -
AM6000N



Repeating remote panel for addressed control units of the AM series. Graphic LCD display 320 x 240. It allows the recognition of the alarm and also the acknowledgment of outputs and the reset of the alarms with code complying with EN54-2. Power supply 10-30Vcc. Absorption at rest of 30mA and in alarm of 80mA.
 Dimensions: 180 x 168 x 55.

NOTIFIER
 by Honeywell

ART.NO.NFXI-OPT
OPTICAL DETECTOR



Addressed analog optical detector consisting of an optical chamber sensitive to light diffusion. Equipped with advanced digital protocol that guarantees greater management possibilities, capacity and flexibility. Double tricolor LED (red, green and yellow) for flashing or fixed programmable 360 ° visualization. Addressing by rotating selectors.
 Equipped with a short-circuit isolator. CPR certificate according to EN54 regulations part 7 and 17. Power supply 15-32VDC. Operating temperature from -30 to + 70 ° C. Relative humidity up to 93% without condensation. Height 52 mm and diameter of 102 mm with installed base.

NOTIFIER
 by Honeywell

ART.NO.NFXI-TDIFF
RATE - OFF - RISE
THERMAL DETECTOR



Indirect analogue thermovelocimetric detector consisting of a double thermistor. Intervention with fast temperature increase (10 ° C per minute) or at 58 ° C. Equipped with advanced digital protocol that guarantees greater management possibilities, capacity and flexibility. Double tricolor LED (red, green and yellow) for flashing or fixed programmable 360 ° visualization. Addressing by rotating selectors. Equipped with a short-circuit isolator. CPR certificate according to EN54 regulations, part 5 and 17. Power supply 15-32VDC. Operating temperature from -30 to + 70 ° C. Relative humidity up to 93% without condensation. Height 61 mm and diameter of 102 with installed base.

NOTIFIER
 by Honeywell

ART.NO.VGS.AD-PR
DETECTOR PROPANE
BOX CONTAINER EEx-d



Propane detector in ADPE container. The catalytic type sensor guarantees alarm signals via a 4-20 mA proportional output. Connectable on central units addressed through a specific module. Possible use with relay board on double threshold control panels with 10 mA pre-alarm and 20 mA alarm. Operating voltage 12-24VDC. Absorption 90 mA. Operating temperature from -10 ° C to + 55 ° C. Relative humidity up to 90%. CESI ATEX certification for AD detectors.

NOTIFIER
 by Honeywell